



Page 1 of 6

 Olin Brass SDS No.:00018.0001
 Review Date: 1/1/15

 Revision No.: 14
 Revision Date: 6/1/15

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: STAINLESS STEEL ALLOY

Chemical Name: Metal Alloy

Synonyms: Stainless Steel Alloys

Chemical Family: Metal/Mixture

Formula: Not applicable - mixture
Product Use: Metallurgical Products

COMPANY ADDRESS SDS Control Group TECHNICAL EMERGENCY TELEPHONE NUMBER:

Olin Brass INFORMATION: 1-618-258-5167

305 Lewis and Clark Blvd 618-258-5654 East Alton, IL 62024-1197

www.olinbrass.com

2. HAZARD IDENTIFICATION

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

Health hazards associated with this product only apply in a fume or dust form.

Classification of the substance or mixture(Fume or Dust)

OSHA HCS 2012

Flammability - 0

Health - 1

Physical - 0

Label elements

OSHA HSC 2012





Hazard Statements

Causes skin irritation - H315

May cause respiratory irritation - H335

Precautionary statements

Avoid breathing dust or fumes - P261

Prevention

Avoid breathing dust or fumes - P261

Do not get in eyes, on skin, or on clothing - P262 In case of inadequate ventilation wear respiratory

protection - P285



Response

EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.- P305 + P351 + P338

If eye irritation develops, Get medical advice/attention - P313

SKIN CONTACT: Rinse skin with water/shower - P353

Take off contaminated clothing and wash before reuse - P362

If skin irritation or rash develops, get medical advice/attention - P363

INHALATION: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing - P340

Get medical advice/attention - P313

INGESTION: Not a likely route of exposure for finished metal alloy. If dust is

ingested, immediately drink water to dilute.

Get medical advice/attention - P363

NOTE TO PHYSICIANS: There is no specific antidote to the active ingredients in this product; use

symptomatic treatment.

Other Hazards

OSHA HSC 2012

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication

Standard), this product is considered hazardous.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Exposure to dust or fume may aggravate an existing dermatitis, asthma, emphysema, or other respiratory disease.

Canada

According to WHMIS

Classification of the substance or mixture

WHMIS

This product is considered to be a manufactured article and therefore not subject to WHMIS requirements.

Other Information

NFPA

Not rated

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS Number	Components	% By Weight	EINECS/ ELINCS	EU Classification	
			#	Symbol	R-Phrase
7440-47-3	Chromium (non-hexavalent	16 - 30	231-157-5	None	None
7439-89-6	Iron	1 - 33	231-096-4	None	None
7439-98-7	Molybdenum	1 - 5	231-107-2	None	None
7439-96-5	Manganese	1 - 5	231-105-1	None	None
7440-02-0	Nickel	6 - 25	231-111-4	Xn	R 40-43
7440-21-3	Silicon	0.15- 2	231-130-8	None	None

OSHA REGULATORY STATUS: In solid form, not hazardous. Dust or fume: carcinogen, irritant, lung toxin, neurotoxin, sensitizer



FIRST AID MEASURES

EYE CONTACT: Immediately flush out fume and dust particles with large amounts of water

for at least 15 minutes, occasionally lifting the upper and lower

eyelids. If eye irritation develops, call a physician at once.

If exposed to dust or fumes, wash skin with plenty of water. Remove SKIN CONTACT:

contaminated clothing and shoes and launder before reuse. If skin irritation or rash develops and persists or recurs, get medical

INHALATION: If symptoms of lung irritation occur (coughing, wheezing or breathing

difficulty), remove from exposure area to fresh air immediately. If

breathing has stopped, perform artificial respiration. Keep affected person

warm and at rest. Get medical attention.

Not a likely route of exposure for finished metal alloy. If dust is INGESTION:

ingested, immediately drink water to dilute. Consult a physician if

symptoms develop.

NOTE TO PHYSICIANS: There is no specific antidote to the active ingredients in this product; use

symptomatic treatment.

FIRE FIGHTING MEASURES

PROPERTY	VALUE	PROPERTY	VALUE
Explosive	No	Flammable	No
Combustible	No	Pyrophoric	No
Flash Point (°C):	Not applicable	Burning Rate of Material:	Not applicable
Lower Explosive Limit:	Not applicable	Autoignition Temp.:	Not applicable
Upper Explosive Limit:	Not Applicable	Flammability Classification: (defined by 29 CFR 1910.1200)	Not applicable

UNUSUAL FIRE AND EXPLOSION HAZARDS:

EXTINGUISHING MEDIA:

Dust may cause an ignitable and/or an explosive atmosphere. For localized powder fires, smother with dry sand, dry dolomite, sodium chloride or soda ash. Use fireextinguishing media appropriate to fight surrounding

SPECIAL FIREFIGHTING PROCEDURES:

None required.



6. ACCIDENTAL RELEASE MEASURES

FOR ALL TRANSPORTATION ACCIDENTS, CALL (618)258-5167. In dust form, this product may be an explosion hazard. Remove all sources of ignition. Dust of fume may be suppressed by the use of a local exhaust system. Dispose of per guidelines under Section 13, WASTE DISPOSAL.

7. HANDLING AND STORAGE

HANDLING: Avoid dispersion of dust in air.

STORAGE: No special requirements.

Shelf Life Limitations: None known. Incompatible Materials for None known.

Packaging:

Incompatible Materials for Storage None known.

or Transport:

OTHER PRECAUTIONS: Do not shake clothing, rags or other items to remove dust.

Dust should be removed by washing or HEPA vacuuming.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	CHEMICAL NAME	ACGIH TLV	OSHA PEL	INTERNATIONAL OELS
7440-47-3	Chromium (non- hexavalent	0.5 mg/m ³	$1~{\rm mg/m}^3$	Belgium, Denmark, France, Japan, Netherlands, Sweden, U.K 0.5 mg/m ³ Finland - 0.1 mg/m ³
7440-02-0	Nickel	1.5 mg/m³ (inhalable)	1 mg/m³	Germany, MAK = 1 mg/m³ Canada (B.C.), Czechoslovakia, Denmark, Norway - 0.05 mg/m³, K1, sensitizer Poland = 0.25 mg/m³ Ireland, Sweden, Switzerland, U.K. = 0.5 mg/m³ Belgium, Canada (Alberta & others), Finland, Japan, Mexico, Netherlands - 1 mg/m³ Portugal = 1.5 mg/m³
7439-89-6	Iron	None established	None established	None established
7439-98-7	Molybdenum	10 mg/m ³ (inhalable) 3 mg/m ³ (respirable)	None established	None established
7439-96-5	Manganese	0.2 mg/m ³	Ceiling - 5 mg/m³	Belgium, Denmark, Finland, France, Switzerland, U.K 1 mg/m ³ Sweden - 2.5 mg/m ³ Germany (MAK) - 0.5 mg/m ³
7440-21-3	Silicon*	10 mg/m³	15 mg/m³	Belgium, Denmark, France, Netherlands, U.K 10 mg/m ³ Switzerland - 4 mg/m ³

*This substance is regulated by OSHA as a Particulate Not Otherwise Regulated (PNOR). The exposure limits listed for both OSHA and ACGIH refer to total dust; the OSHA PEL for the respirable fraction is $5~\text{mg/m}^3$.

ENGINEERING CONTROLS: Local exhaust ventilation is recommended if significant dusting

occurs or fumes are generated. Otherwise, use general exhaust

ventilation.

EYE / FACE PROTECTION: Use safety glasses.

SKIN PROTECTION:
Wear impervious (cut-resistant) gloves and other protective

clothing (aprons, coveralls) as appropriate to prevent skin contact when using this product. If generating a dust, wash thoroughly after handling, especially before eating, drinking, or

smoking.





RESPIRATORY PROTECTION:

SDS #0016.0001 Fage 5 01 0

Respiratory protection not normally needed. If dusting occurs or fumes are generated above the PEL/TLV, use a NIOSH-approved half-

face or full-face respirator equipped with High Efficiency

Particulate (HEPA) filter cartridges.

GENERAL HYGIENE CONSIDERATIONS: Do not eat, drink, or smoke while using this product in dust

form.

9. PHYSICAL AND CHEMICAL PROPERTIES

PROPERTY	VALUE	PROPERTY	VALUE
Appearance: Odor:	Silvery metallic None	Vapor Density (air = 1):	Not applicable No data
		Boiling Point (°F):	
Molecular Weight:	Not applicable - Mixture	Melting point:	1371 - 1454°C (2500 - 2650°F)
Physical State:	Solid	Specific gravity (g/cc):	7.75 - 8.027
pH:	Not applicable	Bulk Density	7.75 - 8.027g/cc
Vapor Pressure (mm Hg):	Not applicable	Viscosity (cps):	Not applicable
Vapor Density	Not applicable	Decomposition	Not applicable
		Temperature:	
Solubility in Water (20	Negligible	Evaporation Rate:	Not Applicable
°C):			
Volatiles, Percent by	Not applicable	Octanol/water partition	Unknown
volume:		coefficient:	

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal temperatures and pressure.

CONDITIONS TO AVOID: Avoid contact with carbon monoxide, particularly at temperatures

between 50°C and 300° C, to prevent formation of nickel

carbonyl which is toxic and a carcinogen.

MATERIALS TO AVOID: Acetylene, chlorine

HAZARDOUS DECOMPOSITION

PRODUCTS: When heated to decomposition, may produce metal oxides

and fumes.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

POTENTIAL EXPOSURE ROUTES: For dust: ingestion, inhalation, and eye contact. For fume: inhalation and eye contact. The finished alloy metal is not hazardous.

ACUTE ANIMAL TOXICITY DATA:

For Product:		For Components						
		Chromium	Iron	Molybdenum	Nickel	Manganese	Silicon	
Oral LD ₅₀	Believed to be > 5 g/kg	27.5 mg/kg (rat)	30 g/kg (rat)	No data	> 5 g/kg (rat)	9 g/kg (rat)	3.16 g/kg (rat)	
Dermal LD ₅₀	Believed to be > 2 g/kg	No data	No data	No data	> 7.5 g/kg (rabbit subcutan- eous)	No data	No data	
Inhalation LC_{50}	Believed to be slightly to moderately toxic	87 mg/m ³ (4 hrs, rat)	No data	No data	> 12 mg/kg (rat, intratra- cheal)	No data	No data	



For Product:		For Components					
		Chromium	Iron	Molybdenum	Nickel	Manganese	Silicon
Irritation	Eye and respiratory irritant	Respira- tory and nasal irritant	Eye irri- tant	No data	Respira- tory irritant, skin sensiti-	Mild skin & eye irritant	Eye, skin, respire- tory irritant

nickel as a known human carcinogen.

SUBCHRONIC/ CHRONIC TOXICITY:

No information for product.

CARCINOGENICITY:

In laboratory animal studies, chronic exposure to high concentrations of nickel has caused an increase in lung and nasal tumors. The International Agency for Research on Cancer (IARC) has classified nickel as possibly carcinogenic to humans, group 2B. The National Toxicology Program (NTP) classifies

MUTAGENICITY:

This product is not known or reported to be mutagenic. Nickel

has been shown to be mutagenic in in vitro studies.

REPRODUCTIVE, TERATOGENICITY, OR DEVELOPMENTAL EFFECTS:

This product is not known or reported to cause reproductive or developmental effects. Exposure of male rats to high concentrations of nickel caused testicular degeneration. However, symptoms of systemic toxicity including severe weight loss, were also observed at the same concentrations

indicating

NEUROLOGICAL EFFECTS:

This product is not know or reported to cause neurological effects. Chronic exposure to very high concentrations of manganese dust has caused nervous system effects including muscle weakness, tremors, and behavioral changes in humans.

INTERACTIONS WITH OTHER

CHEMICALS WHICH ENHANCE TOXICITY:

None known or reported.

12. ECOLOGICAL INFORMATION

ECOTOXICITY: No data is available on this product. Individual constituents are as follows:

Nickel: 96 hr LC₅₀, rainbow trout =31.7 mg/L; 96 hr LC₅₀, fathead minnow = 3.1

mg/L; 72 hr EC_{50} , freshwater algae (4 species): = 0.1 mg/L; 96 hr LC_{50}

, Daphnia = 0.51 mg/L

Chromium: Daphnia magna, 48 hr. LC₅₀ = 0.022 mg/L; Fathead minnow, 96 hr LC₅₀ =

39 mg/L

MOBILITY: No

data

PERSISTANCE/DEGRADABILITY: No

data

BIOACCUMULATION: Chromium, BCF = 10 after 24 days in

trout.

13. DISPOSAL CONSIDERATIONS

If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste of Subpart C, nor is it listed as a hazardous waste under Subpart D. Care must be taken to prevent environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and non-hazardous wastes. This product may be a candidate for metal reclamation.



SDS #0018 0001 Page 7 of 6

14. TRANSPORT INFORMATION

	U.S. DOT	RID/ADR	IMDG	IATA	IMO	Canada TDG
PROPER SHIPPING NAME:			Not reg	gulated		
HAZARD CLASS:						
UN NO.:						
PACKING GROUP:						
LABEL:						
REPORTABLE QUANTITY:						

15. REGULATORY INFORMATION

US FEDERAL

TSCA	The components of inventory.	The components of this product are listed on the Toxic Substance Control Act inventory.					
CERCLA:		Nickel, R.Q. = 100 lbs; Chromium, R.Q. = 5000 lbs. (No reporting is required if diameter of the pieces of metal is equal to or exceeds 100 micrometers (0.004 inches).					
SARA 313:	Nickel, Chromium,	Manganese					
SARA 313 Hazard	Health:	Acute -	Fire:	Reactivity:	Release of		
Class:	For dust or fume only						
SARA 302 EHS List:	None of the compo	None of the components of this product are listed.					

^{*}RQ = Reportable Quantity

STATE RIGHT-TO-KNOW STATUS

Component	*CA Prop. 65	New Jersey	Pennsylvania	Massachusetts	Michigan
Nickel	X	X	X	X	X
Chromium (non-hexavalent)	Not listed	X	X	X	X
Iron	Not listed	Not listed	Not listed	Not listed	Not listed
Molybdenum	Not listed	Not listed	X	X	Not listed
Manganese	Not listed	X	X	X	Not listed
Silicon	Not listed	Not listed	X	X	Not listed

^{* &}quot;WARNING: This product contains detectable amounts of a chemical(s) known to the State of California to cause cancer and/or birth defects or other reproductive harm."

EUROPEAN REGULATIONS

This material is classified as: **Xn, Harmful.** However, this material in its massive solid form is not required to be labeled under EC regulations.

German WGK Classification: Unknown

CANADIAN REGULATIONS

IDL:

DSL LIST: The components of this product are on the DSL or are exempt from reporting under the

New Substances Notification Regulations. Nickel, Chromium, Manganese, Molybdenum

WHMIS: This product is considered to be a manufactured article and therefore not subject to

WHMIS requirements.

16. OTHER INFORMATION

REVISED: Format revised 6/1/15

PREPARED BY: Olin Brass

NOTICE: THE INFORMATION IN THIS SDS SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. OLIN BRASS BELIEVES THIS INFORMATION TO BE RELIABLE AND CURRENT AS OF THE DATE OF PUBLICATION, BUT MAKES NO WARRANTY THAT IT IS.

This document reviewed annually.